

Application No. 10/634,041
Amendment dated 05/17/2005 responding to Office Action dated 05/13/2005

AMENDMENTS

In the Claims

Claims 3-9, 11-12, 15-24, and 26-28 are pending in the application; Claims 1-2, 10, 13-14, and 25 have previously been cancelled.

Please cancel claim 3 without prejudice, and amend claim 4, 8, 9, and 11 as indicated below.

This listing of Claims will replace all prior versions and listings of Claims in the application.

Application No. 10/634,041

Amendment dated 05/17/2005 responding to Office Action dated 05/13/2005

LISTING OF THE CLAIMS

1. (Cancelled)

2. (Cancelled)

3. (Cancelled)

4. (Currently Amended) A suspension for use with a vehicle which travels in a longitudinal direction, the suspension comprising: ~~The suspension of claim 3~~
a lower fork tube;
an upper fork tube slidably coupled to the lower fork tube, wherein one of the fork tubes is disposed partially within the other; and
a fork bottom having a substantially semi-cylindrical fork bottom body rigidly coupled to the lower fork tube and having different stiffness in the longitudinal direction than in a lateral direction generally perpendicular to the longitudinal direction;
wherein the longitudinal stiffness is greater than the lateral stiffness; and
wherein the fork bottom further ~~comprises~~ comprises means for adjusting a lateral stiffness of the fork bottom body.

5. (Original) The suspension of claim 4 wherein the means for adjusting comprises:
a tension cable having a lower end coupled to a lower end of the fork bottom body and an upper end coupled to an upper end of the fork bottom body; and
the fork bottom body including a fulcrum over which the tension cable is stretched.

6. (Original) The suspension of claim 5 wherein the means for adjusting further comprises:
a threaded adjuster coupled to the tension cable for adjusting tension on the tension cable.

7. (Original) The suspension of claim 4 wherein the means for adjusting comprises:
a tension rod having a lower end coupled to a lower end of the fork bottom body and an upper end coupled to an upper end of the fork bottom body, whereby at least one of tension and pressure may be applied to the fork bottom by the tension rod.

Application No. 10/634,041

Amendment dated 05/17/2005 responding to Office Action dated 05/13/2005

1 8. (Currently Amended) The suspension of ~~claim 3~~ claim 4 further comprising:
2 a fulcrum coupled to the fork bottom; and
3 a tension cable coupled to the fork bottom and placed under tension against the fulcrum
4 to impart lateral pressure against the fork bottom.

1 9. (Currently Amended) The suspension of ~~claim 3~~ claim 4 wherein:
2 the lower fork tube is disposed within the upper fork tube.

1 10. (Cancelled)

1 11. (Currently Amended) The suspension of ~~claim 3~~ claim 4 wherein the vehicle comprises:
2 a two-wheeled vehicle.

1 12. (Original) The suspension of claim 11 wherein the two-wheeled vehicle comprises:
2 a motorcycle.

1 13. (Cancelled)

1 14. (Cancelled)

1 15. (Previously Amended) A two-wheeled vehicle comprising:
2 a frame including a steering tube;
3 an upper triple clamp rotatably coupled to the steering tube;
4 a lower triple clamp rotatably coupled to the steering tube;
5 a pair of sliding tube forks coupled to the triple clamps;
6 a wheel assembly including a wheel coupled to an axle; and
7 a pair of fork bottoms non-telescopingly coupling the forks to the axle, wherein the fork
8 bottoms have different stiffness in a longitudinal direction of travel of the two-wheeled vehicle
9 than in a lateral direction substantially parallel to the axle;
10 wherein the stiffness in the longitudinal direction is greater than the stiffness in the lateral
11 direction;
12 wherein at least one of the fork bottoms comprises,
13 a fulcrum, and

Application No. 10/634,041

Amendment dated 05/17/2005 responding to Office Action dated 05/13/2005

14 a tension cable stretched over the fulcrum, placing the fork bottom under
15 end-to-end tension such that the fulcrum provides side-to-side pressure on the fork
16 bottom to increase sideways stiffness of the fork bottom.

1 16. (Original) The two-wheeled vehicle of claim 15 wherein the at least one of the fork bottoms
2 further comprises:
3 an adjuster for changing tension on the tension cable to adjust the sideways stiffness of
4 the fork bottom.

1 17. (Original) The two-wheeled vehicle of claim 16 wherein:
2 both of the fork bottoms comprise a fulcrum, tension cable, and adjuster.

1 18. (Original) The two-wheeled vehicle of claim 17 wherein the two-wheeled vehicle comprises:
2 a motorcycle.

1 19. (Previously Amended) The two-wheeled vehicle of claim 15 wherein:
2 upper ends of the fork bottoms extend upward beyond an uppermost point of the outer
3 diameter of the wheel.

1 20. (Previously Amended) The two-wheeled vehicle of claim 15 wherein:
2 the fork bottoms are longer than inner sliding tubes of the forks.

1 21. (Original) A method of adjusting side-to-side flex of a two-wheeled vehicle suspension, the
2 suspension including a sliding tube fork coupled to a fork bottom, the method comprising:
3 adjusting end-to-end tension on a tension cable which is coupled to both ends of the fork
4 bottom and stretched over a fulcrum between the ends of the fork bottom;
5 whereby side-to-side pressure exerted by the tension cable on the fulcrum, and by the
6 fulcrum on the fork bottom, is adjusted.

1 22. (Original) The method of claim 21 wherein adjusting the tension on the tension cable is
2 accomplished by:
3 turning a threaded tension adjuster which couples one end of the tension cable to the fork
4 bottom.

Application No. 10/634,041

Amendment dated 05/17/2005 responding to Office Action dated 05/13/2005

1 23. (Previously Amended) A fork bottom comprising:

2 a body having different longitudinal stiffness than lateral stiffness;

3 means at an upper end of the body for coupling to a fork tube;

4 means at a lower end of the body for coupling to an axle;

5 a tension cable;

6 means at the upper end of the body for coupling to an upper end of the tension cable;

7 means at the lower end of the body for coupling to a lower end of the tension cable; and

8 a fulcrum substantially in a middle of the body.

1 24. (Original) The fork bottom of claim 23 wherein:

2 the longitudinal stiffness is greater than the lateral stiffness.

1 25. (Cancelled)

1 26. (Previously Amended) The fork bottom of claim 23 wherein the fulcrum comprises:

2 means for positioning the tension cable.

1 27. (Previously Amended) The fork bottom of claim 23 further comprising:

2 an adjuster coupled to the upper end of the tension cable and to the upper end of the

3 body, for adjusting tension on the tension cable.

1 28. (Original) The fork bottom of claim 23 further comprising:

2 a lower fork tube integrally formed with the body.